



**ULTRA**

**ULTRA MODULAR ENTRANCE PANEL**



ULTRA, the new and most technologically advanced entrance panel offering maximum ease of installation. This modular entrance panel features a modern design, created to adapt to a wide range of applications, from small to large complexes. Die-cast aluminium frames increase the entrance panel's resistance to atmospheric agents. Available in flush-mounting or surface-mounting versions (surface-mounting variant just 35 mm thick). Easy to install and configure, thanks to the smart programming of call buttons. Available in an audio and audio/video version with colour video camera. The buttons are made using professional-grade plastic given an anti-yellowing and anti-dulling treatment, or aluminium. Twilight sensor for automatic nameplate backlight switch-off during daytime hours.

**AWARDS**

DESIGN  
MILANO





**ULTRA**

**ULTRA MODULAR ENTRANCE PANEL**

**GENERAL DATA**

Type	External unit modular
Height (mm)	315
Width (mm)	126
Depth (mm)	53.5
Product color	Aluminium, Black RAL9005, Gray RAL 7042
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

**AUDIO FEATURES**

Microphone	MEMS audio digital sensor, omnidirectional
Loudspeaker	28mm (Ø), 8 Ohm, 1W (2)

**CAMERA FEATURES**

Camera	Colours
Sensor type	1/3" CMOS
Lens optical dimensions (mm)	2.8
Angle of view (H x V - °)	120 x 90
Sensitivity	0.5 (colour)

**ELECTRICAL CHARACTERISTICS**



**ULTRA**

**ULTRA MODULAR ENTRANCE PANEL**

Supply voltage	33VDC
----------------	-------

**HARDWARE FEATURES**

Call type	Push-buttons
Type of buttons	Mechanical
Backlight colour	White, Off
Communication ports	Micro-USB
Twilight sensor	Yes

**SETTINGS**

Loudspeaker volume	Yes
Microphone volume	Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IP protection rating	IP65
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**MAIN FUNCTIONS**

Door opener	Yes
Input for local door release button	Yes
Door open signaling input	Yes
Visual indications of system status	Yes